

HD 525 S PRESSURE WASHER



HD 525 S

Economical and powerful high-pressure cleaning

When cleaning applications call for a technique beyond the capability of sweeping, scrubbing, and vacuuming, high-pressure cleaning is often the answer. Pressure washers channel the power of water to aggressively tackle some of the most challenging tasks faced by cleaning professionals. Begin with the HD 525 S, Tornado's introductory model in its pressure washer family.

The HD 525 S is an economical package with numerous professional features for commercial applications. An infinitely variable detergent metering system and vario pressure wand provides the operator flexibility in power control. The brass cylinder head, three piston steel pump, pressure switch, and hydro-dynamic seal lubrication have been included in the design for increased efficiency and service life. The pressure switch automatically shuts off the motor when the trigger gun is released. This is a feature only normally seen on premium models.

The HD 525 S has a patented, one-piece motor pump housing that encloses an air-cooled single-phase motor with a built-in motor protection switch. The unit operates off standard 15 amp service and features a collapsible handle, high pressure hose, trigger gun, and spray wand. It fits easily into a car trunk and the high-pressure hose rotates in the trigger gun, eliminating twists and loops in the hose.



Mobility
Two large wheels and a collapsible handle make transport simple and hassle-free.



Value and versatility
From pool decks to vehicles to numerous commercial applications, the HD 525 S offers the convenience and performance of pressure washer cleaning at an extremely competitive price.



HD 525 S

Smart features

The pressure gauge is located in the trigger gun and allows continuous monitoring of the operating pressure. Releasing the trigger during operation shuts off the motor, eliminating pump and motor damage seen in competitive units.

PRODUCT SPECIFICATIONS

MODEL	CATALOG NUMBER	OPERATING PRESSURE (INFINITELY VARIABLE)	ENGINE	WATER FLOW VOLUME	MAXIMUM WATER SUPPLY TEMP.	SERVICE REQUIREMENT	WEIGHT	SIZE (L X W X H)
HD 525 S	97220	150-1250 PSI	1.6 HP	1.8 GPM	140 F	15 AMPS	33.1 LBS.	20" X 9" X 11"

STANDARD ACCESSORIES AND ATTACHMENTS

(Included with unit)

MODEL	33' HIGH PRESSURE	TRIGGER GUN	SPRAY WAND AND
	HOSE	(with PRESSURE GAUGE)	NOZZLE ASSEMBLY
HD 525 S	K6389853	K4775296	K4760387

OPTIONAL ACCESSORIES AND REPLACEMENT ITEMS

MODEL	DIRTBLASTER NOZZLE	SPRAY WAND FOR USE OF	50' EXTENSION HOSE	HOSE
	(REQUIRES 4760356 FOR USE)	DIRTBLASTER NOZZLE	(REQUIRES 4403002)	COUPLER
HD 525 S	K4763931	K4760356	K6390010	K4403002

