



Innovative Cleaning Systems
www.tornadovac.com

HD 655 FOOD SERVICE PRESSURE WASHER



HD 655

HD 655 FOOD SERVICE PRESSURE WASHER

The power of high-pressure cleaning, designed for the demands of food service applications

The HD 655 is an electric-powered pressure washer designed for the food service industry and other applications where cleaning with in-house hot water is a must. The unit can be hooked up to a hot water source and accepts water up to 185° F. The unit is perfect for use in kitchens, meat rooms, and other applications in the food service industry.

The HD 655 is a powerful package loaded with professional features for commercial applications. Low-pressure chemical injection, infinitely variable detergent metering system and triple changeover pressure wand provide the operator maximum flexibility.

The brass cylinder head, three piston steel pump, and pressure switch have been included in the design for increased efficiency and service life. The pressure switch automatically shuts off the motor when the trigger gun is released, protecting the unit from damage. An overflow safety valve protects the unit against excessive high pressure.

The HD 655 has a patented, one-piece motor pump housing that encloses an air-cooled single-phase 4-pole, 2.1 HP motor. The unit requires a 20 amp outlet and 20 amp service. The HD 655 has a cage frame design for maximum protection, as well as a food service-grade high-pressure hose, trigger gun with pressure gauge, and stainless steel wand.



HD 655

Customized for food service

A heavy-duty powder-coated frame with stainless steel splash protection is designed to withstand challenging applications in demanding operating environments. The unit has four rubber legs for shock absorbency and can easily be wall-mounted. The cover cutout permits easy lubrication level check.



Versatile

The triple changeover nozzle has settings for pencil jet, fan jet, and chemical injection. The HD 655 has infinitely adjustable pressure from 300 to 1450 psi.



Convenient

The trigger gun and wand fit snugly and securely in the built-in holder.



Smart features

The pressure gauge is located in the trigger gun and allows continuous monitoring of the operating pressure. Releasing the trigger during operation shuts off the motor, eliminating pump and motor damage seen in competitors units.

PRODUCT SPECIFICATIONS

MODEL	CATALOG NUMBER	OPERATING PRESSURE (INF. VARIABLE)	MOTOR (4-POLE)	WATER FLOW VOLUME (INF. VARIABLE)	MAX. WATER SUPPLY TEMP.	VOLTAGE/OUTLET REQUIREMENTS	DETERGENT SIPHON	AUTO SHUT-OFF	WEIGHT	SIZE (L X W X H)
HD 655	97230	300-1450 PSI	2.1 HP	0.6-2.2 GPM	185° F	18.7/20 AMPS	Low Pressure	Standard	49 lbs.	20" X 14" X 17"

STANDARD ACCESSORIES AND ATTACHMENTS

(Included with unit)

MODEL	50' HIGH PRESSURE HOSE	TRIGGER GUN W/PRESSURE GAUGE	SPRAY WAND AND NOZZLE ASSEMBLY	TRIPLE CHANGEOVER NOZZLE
HD 655	K6390445	K4775296	K4760356	K4763987

OPTIONAL ACCESSORIES

MODEL	DIRTBLASTER NOZZLE
HD 655	K4763252



Tornado Industries • 7401 W. Lawrence Ave., Chicago, IL 60706 • 1-800-VACUUMS or (708) 867-5100 Fax: (708) 867-6968
Visit our web site at: www.tornadovac.com